

# MioCARE<sup>+</sup>

## A335

2D Barcode Reader

Pocket sized tablet computer  
designed for healthcare



### Unified Communication

3G, WIFI and Bluetooth® 4.0 connected.

### IP54 Rugged and Cleanable

Water, dust, 1 meter drop resistant and anti-microbial.

### Open & Flexible

Uses Android™ 4.2. with SDK and emulator support.

### Integrated Data capture

NFC, HF RFID and 2D barcode built into workflows.

# MioCARE<sup>+</sup>

## A335

### 2D Barcode Reader

Pocket sized tablet computer  
designed for healthcare

Introducing the new 5.88" touch screen tablet  
from MioCARE with 3G and WIFI.

The A335 includes integrated NFC and a 2D barcode scanner offering data capture built right into your workflow. This gives real-time and context aware reporting and data retrieval offering significant error reduction. Integrated AGPS adds location awareness.

With 3G and WiFi connectivity the MioCARE A335 is always connected indoors and out. The cradles designed for healthcare are fast charging and allow the A335 to be always available.



#### Package contents:

- Device
- AC mains charger
- USB to Mini USB cable
- Printed quick start guide
- Printed warranty & end user license agreement



6-units device cradle for power charging  
and data synchronization

### Unified Communication

3G, WiFi and Bluetooth® 4.0. connected.

### IP54 Rugged and Cleanable

Water, dust, 1 meter drop resistant and anit-microbial

### Open & Flexible

Uses Android™ 4.2 with SDK  
and Emulator support.

### Integrated Data capture

NFC, HF RFID and 2D barcodes  
built into workflows.

### System

Screen:	5.88" Capacitive, WVGA (800 x 480), 350 nits
OS:	Android™ 4.2
Processor:	TI OMAP4470 1.5GHz
Location:	UBlox U200 A-GPS
Battery:	3000mAh capacity, up to 6 hours operation, charge via mini USB
RAM:	1GB
Memory:	Internal 16GB Expandable: MicroSD SDHC up to 32GB
Connectivity:	3G, Wireless 802.11 a/b/g/n (2.4 & 5GHz), Bluetooth® 4.0
Input:	Mini USB, Micro HD Interface
Sensors:	2D barcode imager, Accelerometer Near field communication (NFC), GPS
Environment:	IP54, 1M drop resistant
Camera:	Rear 5.0Mp AF / Front 1.2Mp FF
Audio:	Mono speaker, 3.5mm jack, microphone
AC mains:	In: 100~240VAC Out: 5VDC, 2A Mini USB
Operating temperature:	-10 to +50°C (Camera function: -10 to +45°C )
Certification:	CE/CB - CE (R&TTE), FCC, NCC/BSMI, CCC, IP54, EN60601*, Cisco CCX*
Warranty:	12 months (extended warranty available)
Dimensions:	200 (h) x 99 (w) x 15mm (d)
Weight:	370g

\* Optional



**MiTAC International Corp.**

©2014 MITAC Intl. All rights reserved. Android is a trademark of Google Inc. All other trademarks are the property of their respective owners.  
All specifications are subject to change without prior notice.