




# MioWORK<sup>™</sup> L110/115

## Rugged enterprise computing

The L110/115 from MioWORK is a high performance enterprise tablet. Featuring an IP54 ingress-resistant design, the L110/115 enables an all-day usage in the field. Through the 10.1" capacitive touchscreen, users can see more content on a larger screen. Programmable hotkeys allow faster accuracy for key functions and applications. The L110/115 includes dual-band WiFi for use on 5GHz enterprise networks and the integrated 3G\* enables field workers to always be connected. With up to 8 hours battery life and a hot-swap user-replaceable battery, the L110/115 is the optimal solution for uninterrupted use in demanding conditions.



### Designed for professionals

- Hot swap battery for uninterrupted use
- Robust design  
IP54 sealed / 1.2m drop resistant



### Connected anywhere

- Connectivity with 3G\*
- WiFi and Bluetooth® 4.0



### Comprehensive using scenario

- Designed for usage in various fields, including:  
Mobile POS, Table ordering, Field Service, Transportation and Logistics, Golf course navigation and Location based services and many more.

\* Only available on the L115 model.



## Specifications **L110**

## **L115**

<b>Display</b>	10.1" 1280x800 WXGA TFT (400nits)	10.1" 1280x800 WXGA TFT (400nits)
<b>Touch Panel</b>	Capacitive Touch Screen	Capacitive Touch Screen
<b>Platform</b>	TI OMAP 4470 1.5GHz	TI OMAP 4470 1.5GHz
<b>OS</b>	Android 4.2.2	Android 4.2.2
<b>Memory</b>	1GB RAM / 16GB ROM	1GB RAM / 16GB ROM
<b>Expansion</b>	User accessible MicroSD up to 32GB SDHC	User accessible MicroSD up to 32GB SDHC
<b>Wireless Interface</b>	No Wireless WAN support	Wireless WAN Data UMTS/HSPA 800/850/900/1700/1900/2100 MHz GSM 850/900/1800/1900 Mhz; GPRS/EDGE Class 12
	WiFi 802.11 a/b/g/n	WiFi 802.11 a/b/g/n
	Bluetooth 4.0	Bluetooth 4.0
	N/A	GPS
<b>Sensors</b>	Accelerometer - auto rotation Ambient light sensor Vibrator	Accelerometer - auto rotation Ambient light sensor Vibrator
<b>Camera</b>	N/A	Front: 1.2M fixed focus
<b>Physical Interface</b>	microUSB-B 2.0 USB Type A 2.0 (host and client) MicroSD slot SIM card slot: N/A 10 pogo pins connector Build-in MIC Build-in Speaker Headset jack Power DC-Jack	microUSB-B 2.0 USB Type A 2.0 (host and client) MicroSD slot SIM card slot 10 pogo pins connector Build-in MIC Build-in Speaker Headset jack Power DC-jack (compatible with waterproof vehicle charger only)
<b>Buttons</b>	Side: Power, Volume up/down Front: Function key x 4	Side: Power, Volume up/down Front: Function key x 4
<b>Battery</b>	Rear: Reset switch 6720mAh battery, hot swappable	Rear: Reset switch 6720mAh battery, hot swappable
<b>LED indicator</b>	Battery life - up to 8 hours LED indicator X 2	Battery life - up to 8 hours LED indicator X 2
<b>Environment</b>	IP54 and 1.2m drop resistant to plywood -10~+50°C operating temperature -20~+70°C (exclude LCM, Battery, Camera) Humidity : 0~90%, Non-Condense Altitude : Operating: 0~10,000ft	IP54 and 1.2m drop resistant to plywood -10~+50°C operating temperature -20~+70°C (exclude LCM, Battery, Camera) Humidity : 0~90%, Non-Condense Altitude : Operating: 0~10,000ft
<b>Standard Accessory</b>	Power adapter with power cord (UK, EU) USB cable	Power adapter with power cord (UK, EU) USB cable
<b>Certification</b>	CE, IP54	CE, IP54
<b>Warranty</b>	12 months (extended warranty available)	12 months (extended warranty available)
<b>Weight</b>	935g	950g
<b>Dimensions</b>	276.7x200x19.6mm	276.7x200x19.6mm